



718 Park East Drive, Woonsocket, RI 02895 USA  
 Phone: +1 (401)-726-4500  
 Email: info@epoxyset.com www.epoxyset.com

# FLASHBOND™

## UV-6502CL

(Formerly BP026502)

### UV CURE EPOXY

**TECHNICAL DATA** **SEPTEMBER 2019**

#### Product Description

UV-6502CL is a low viscosity, high clarity, light curing epoxy adhesive that offers excellent strength wetting properties. UV-6502CL cures to a clear polymer and maintains clarity at elevated temperatures. This product requires direct light exposure during cure. Because of the variability of different UV/LED light sources, it is suggested that the user test and specify intensity and exposure time. This product will cures best in the UVA wavelengths (315-365nm).

#### APPLICATIONS

- Electronics
- Encapsulation
- Sealant

#### FEATURES

- RoHS & REACH Compliant
- Excellent Chemical Resistance
- High Bond Strength
- Fast UV Cure

#### SUBSTRATES

- Metals
- Ceramics
- Glass

#### PACKAGING

- Syringes
- Bulk

TYPICAL PROPERTIES OF UNCURED MATERIAL	
Property	Value
Chemical Class	Cationic Epoxy
Appearance	Clear
Viscosity, 20 RPM @ 25°C, cps	200 to 500
Specific Gravity	1.12

TYPICAL PROPERTIES OF CURED MATERIAL	
Property	Value
Glass Transition Temperature (Tg), °C	135
Hardness, Shore	D-82
Ultimate Tensile Strength, PSI	5,000
Elongation at Break, %	4
Operating Temperature Range, °C	-55 to 200
Volume Resistivity, Ω-cm	1 x 10 <sup>14</sup>

**\*All properties given are typical values and are not intended for use in preparing specifications.**

CURE OVERVIEW	
Optimal Wavelength	315, 365nm
Optimal Intensity	100-300 mW/cm <sup>2</sup>

#### SHELF LIFE, STORAGE

23°C ± 5°C      1 Year DOM

MATERIAL IS LIGHT SENSITIVE. CONSULT SDS FOR SAFE HANDLING RECOMMENDATIONS.

#### THIS MATERIAL IS SOLD FOR INDUSTRIAL USE ONLY

EPOXYSET MAKES NO EXPRESS OR IMPLIED REPRESENTATIONS OR WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE, WITH RESPECT TO THIS PRODUCT AND GUARANTEES NO PARTICULAR OUTCOME OR RESULT FROM ITS USE. EPOXYSET'S LIABILITY TO CUSTOMER WITH RESPECT TO THIS PRODUCT SHALL IN NO EVENT EXCEED THE AMOUNT PAID BY CUSTOMER FOR IT.