

FLASHBOND[™] UV-8701E

UV CURE EPOXY

TECHNICAL DATA

Product Description

UV-8701E is a thixotropic, light curing epoxy adhesive that bonds well to a wide variety of substrates including engineered plastics such as Ultem[™], Lexan[™], and ABS. This product exhibits good surface wetting and adhesion to glass and many plastics. UV-8701 is clear magenta when uncured but turns translucent when cured as a built in cure indicator. This product requires direct light exposure during cure. Because of the variability of different UV/LED light sources, it is suggested that the user test and specify intensity and exposure time. This product will cure in the presence of visible light (400-415nm). Can be cured at 150°C for shadowed areas if necessary.

APPLICATIONS

• Electronics

Sealant

- Encapsulation
- RoHS & REACH Compliant Excellent Chemical Resistance
- High Bond Strength

FEATURES

• Fast UV Cure

- SUBSTRATES
- Metals
- Ceramics
- Glass
- Plastics
- PACKAGING

SEPTEMBER 2019

- Syringes
- Bulk

| TYPICAL PROPERTIES OF UNCURED MATERIAL | |
|--|------------------|
| Property | Value |
| Chemical Class | Cationic Epoxy |
| Appearance | Magenta |
| Viscosity, 20 RPM @ 25°C, cps | 5,000 to 9,000 |
| Viscosity, 2 RPM @ 25°C, cps | 15,000 to 20,000 |
| Specific Gravity | 1.14 |

| TYPICAL PROPERTIES OF CURED MATERIAL | | |
|---------------------------------------|----------------------|--|
| Property | Value | |
| Glass Transition Temperature (Tg), °C | 135 | |
| Hardness, Shore | D-78 | |
| Ultimate Tensile Strength, PSI | 5,000 | |
| Elongation at Break, % | 6 | |
| Operating Temperature Range, °C | -55 to 250 | |
| Volume Resistivity, Ω-cm | 1 x 10 ¹⁴ | |

*All properties given are typical values and are not intended for use in preparing specifications.

| CURE OVERVIEW | | |
|--------------------|----------------|--|
| Optimal Wavelength | 400-415nm | |
| Optimal Intensity | 100-200 mW/cm2 | |

SHELF LIFE, STORAGE

18 ± 10°C 1 Year DOM

MATERIAL IS LIGHT SENSITIVE. CONSULT SDS FOR SAFE HANDLING RECOMMENDATIONS.

THIS MATERIAL IS SOLD FOR INDUSTRIAL USE ONLY

EPOXYSET MAKES NO EXPRESS OR IMPLIED REPRESENTATIONS OR WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE, WITH RESPECT TO THIS PRODUCT AND GUARANTEES NO PARTICULAR OUTCOME OR RESULT FROM ITS USE. EPOXYSET'S LIABILITY TO CUSTOMER WITH RESPECT TO THIS PRODUCT SHALL IN NO EVENT EXCEED THE AMOUNT PAID BY CUSTOMER FOR IT.